

NNR 55/45-150 AMT IFS TRAYPACK NNR 45-150 AMT IFS TRAYPACK CREW



Images throughout may not accurately depict actual specification or they may show extra cost options. Refer written content or contact Isuzu for further details.

WEIGHT RATINGS

| | |
|--|------------------|
| GVM (Single Cab) | 5,500 / 4,500 kg |
| GVM (Crew Cab) | 4,500 kg |
| GCM | 8,000 kg |
| TOWING CAPACITY (at 4,500 kg GVM rating) | 4,000 kg* |

ENGINE

| | |
|---------------|----------------------------|
| POWER | 110 kW @ 2,800 rpm |
| TORQUE | 375 Nm @ 1,600 - 2,800 rpm |

TRANSMISSION

6 speed automated manual transmission (AMT)

* Refer to back page for detailed weight rating information

| READY TO WORK | |
|--------------------------|---|
| STANDARD FEATURES | Heavy duty aluminium tray |
| | Integrated load restraint anchor points |
| | Headboard including rear window protector |
| | Removable drop sides and rear tailgate |
| | Isuzu low light capable reversing camera |

| SERVICE AGREEMENTS | | | |
|---|---|-----------------|-------|
| Optional Service Packages | ESSENTIALS | ESSENTIALS PLUS | TOTAL |
| SCHEDULED SERVICINGS | ● | ● | ● |
| CONSUMABLES | | ● | ● |
| ENGINE, TRANSMISSION & DRIVELINE | | | ● |
| EXTRAS | After-hours Servicing, Glass, Fuel Card, Pickup - Dropoff | | |

| INTELLIGENT SAFETY | | |
|--|---|--------------|
| ACTIVE SAFETY ADVANCED DRIVER ASSISTANCE SYSTEMS (ADAS) | Advanced Emergency Braking | (AEB) |
| | Forward Collision Warning | (FCW) |
| | Distance Warning System | (DWS) |
| | Lane Departure Warning | (LDW) |
| | Traffic Movement Warning | (TMW) |
| | Electronic Stability Control | (ESC) |
| | Anti-Skid Regulator | (ASR) |
| | Anti-Lock Braking System | (ABS) |
| | Automatic Lighting System (Front & Rear) | (ALS) |
| | Cab Tilt Warning (Single cab only) | (CTW) |
| PASSIVE SAFETY CABIN OCCUPANT SAFETY SYSTEMS (COSS) | Driver & front passenger airbags | |
| | Driver & front left hand passenger seatbelt pretensioners | |
| | ECE-R29 cab with side anti-intrusion beams | |
| | Overhead shelf restraint netting | |
| | Door mounted cornering lamps | |




Subject to the conditions outlined in the IAL New Vehicle Warranty. For further information please visit isuzu.com.au or contact your local dealer.

| ISUZU CARE | |
|------------------------|--------------------------------------|
| WARRANTY | 6 Year Standard Warranty |
| | 250,000 km / Unlimited Hours |
| | 3 Year / Unlimited km Body Equipment |
| ROADSIDE ASSIST | 6 Year Roadside Support |
| | 24/7 Unlimited km |

NNR 55/45-150 AMT IFS TRAYPACK

NNR 45-150 AMT IFS TRAYPACK CREW

| ENGINE | |
|--------------------------|--|
| DESCRIPTION | Isuzu 4JJ1-TCS |
| TYPE | 4 cylinder 16 valve with chain driven DOHC |
| DISPLACEMENT | 2,999 cc |
| COMPRESSION RATIO | 17.5:1 |
| BORE X STROKE | 95.4 mm x 104.9 mm |
| POWER | 110 kW (150PS) @ 2,800 rpm (DIN NET) |
| TORQUE | 375 Nm @ 1,600 - 2,800 rpm (DIN NET) |
| INDUCTION | Electronically controlled variable nozzle turbocharger with air-to-air intercooler |
| FUEL INJECTION | Direct injection high pressure common rail |
| EMISSION CONTROL | Cooled EGR with exhaust Diesel Particulate Diffuser (DPD). ADR 80/03 (Euro V / EEV) compliant. |



| CLUTCH | |
|------------|---|
| AMT | Type: Fully automated electro/hydraulically controlled wet clutch and torque converter (TC) with lock up |

| TRANSMISSION | | | | | | | | | | | | | | |
|---|---|-------|-------|-------|-------|-------|-----|-----|-------|-------|-------|-------|-------|-------|
| AMT | Description: Isuzu MYY-6E | | | | | | | | | | | | | |
| | Type: 6 speed with both fully automatic and clutchless manual operation modes | | | | | | | | | | | | | |
| | Ratios: | | | | | | | | | | | | | |
| | <table border="1"> <thead> <tr> <th>1ST</th> <th>2ND</th> <th>3RD</th> <th>4TH</th> <th>5TH</th> <th>6TH</th> <th>REV</th> </tr> </thead> <tbody> <tr> <td>5.979</td> <td>3.434</td> <td>2.040</td> <td>1.379</td> <td>1.000</td> <td>0.750</td> <td>5.701</td> </tr> </tbody> </table> | 1ST | 2ND | 3RD | 4TH | 5TH | 6TH | REV | 5.979 | 3.434 | 2.040 | 1.379 | 1.000 | 0.750 |
| 1ST | 2ND | 3RD | 4TH | 5TH | 6TH | REV | | | | | | | | |
| 5.979 | 3.434 | 2.040 | 1.379 | 1.000 | 0.750 | 5.701 | | | | | | | | |
| Power Take Off facility: Provision on LHS of transmission case. Drive from counter gear. | | | | | | | | | | | | | | |

| AXLES | |
|--------------|--|
| FRONT | Description: Isuzu FI026 |
| | Type: Independent wishbone |
| | Capacity: 2600 kg |
| REAR | Description: Single cab: Isuzu R060 Crew cab: Isuzu R050 |
| | Type: Full floating banjo with four differential pinions |
| | Capacity: Single cab: 6,000 kg Crew cab: 5,000 kg |
| | Ratio: 4.556 |

| SUSPENSION | |
|--------------|--|
| FRONT | Coil springs |
| | Double acting hydraulic shock absorbers |
| REAR | Multi leaf main, taper leaf helper spring |
| | Double acting hydraulic shock absorbers. Stabiliser bar. |

| BRAKES | |
|------------------------|---|
| TYPE | Ventilated disc/disc with dual circuit hydraulic control, vacuum assistance and electronic brake force distribution (EBD) |
| DIAMETER FRONT | 293 mm |
| DIAMETER REAR | Single cab: 293 mm Crew cab: 275 mm |
| PARK BRAKE | 190 mm diameter drum mounted on rear of transmission |
| AUXILIARY BRAKE | Vacuum controlled exhaust brake |

| STEERING | |
|---------------------------|--|
| TYPE | Power assisted rack and pinion |
| TURNS LOCK TO LOCK | 4.2 |
| WHEEL LOCK ANGLE | 47.5° (inside wheel) / 39.5° (outside wheel) |

| WHEELS & TYRES | |
|----------------|--|
| FRONT | Wheels: 16 x 5.5J five stud steel |
| | Tyres: 195/85R16 114/112L Michelin XJE4 Mix Energy Tubeless |
| | Steer axle tyre rating: 2,360 kg |
| REAR | Wheels: 16 x 5.5J five stud steel |
| | Tyres: 195/85R16 114/112L Michelin XJE4 Mix Energy Tubeless |
| | Drive axle tyre rating: 4,480 kg |
| SPARE | 1 frame mounted spare wheel and tyre assembly |

| CHASSIS FRAME | |
|-------------------|--|
| TYPE | Cold rivetted ladder frame. SAPH440 steel sidemembers. Rivetless top flange. |
| DIMENSIONS | Side rail (mm): 214 x 70 x 5.0 Rear frame width (mm): 750 |

| FUEL TANK | |
|-----------------|-------------------------------|
| TYPE | Frame mounted steel fuel tank |
| CAPACITY | 100L |
| FUEL CAP | Lockable |

| ELECTRICAL SYSTEM | |
|----------------------|--|
| TYPE | 24 volt |
| ALTERNATOR | 90 amp |
| STARTER MOTOR | 4.0 kW |
| BATTERY | 2 x 80D26L (630 CCA) batteries connected in series |

| CABIN GENERAL FEATURES | |
|--------------------------|--|
| ENGINE ACCESS | Single cab: Manual cab tilt to 45° with torsion bar assistance Crew cab: Access hatch under driver's seat and tiltable front passenger seat |
| STEPS | Heavy duty anti-slip steps |
| DOORS | 90° opening internally reinforced front doors |
| MIRRORS | Heated and powered exterior main mirrors with flat glass and additional independantly adjustable convex "spot" mirrors |
| WIPERS | Two speed windscreen wipers with intermittent wipe mode |
| EXTERIOR LIGHTING | Multi-reflector halogen headlamps Roof mounted clearance lamps |
| AUDIBLE WARNING | Reverse alarm |
| GRILLE | Body coloured |
| SECURITY | Central locking with remote keyless entry and immobiliser |

| CABIN INTERIOR | |
|---------------------------|---|
| SEATING | Single cab: Driver's bucket seat equipped with mechanical suspension and weight adjustment to 130kg Crew cab: Driver's bucket seat Front passenger bench seat with 2 seat capacity Crew cab: Rear bench seat with 4 seat capacity |
| SEATBELTS | 3-point lap sash seatbelts in all outboard seating positions. Centre seat lap belts. |
| STEERING COLUMN | Tilt/telescopic adjustable |
| ENTRY ASSIST GRIPS | Door and roof pillar mounted Crew cab: Full width rear grab rail |
| DOOR WINDOWS | Electric control |
| STORAGE | Overhead shelf Twin cup holders Front centre console box and storage tray Front door pockets |
| POWER OUTLET | 24V cigarette lighter |
| AIRCONDITIONING | Manual control |
| INTERIOR LIGHTING | Single cab: Fluorescent lamp Crew cab: Standard lamp |

| MYISUZU CO-PILOT AUDIO VISUAL UNIT | |
|------------------------------------|---|
| SCREEN TYPE | 10.1" 1080p High Definition with capacitive touch |
| OPERATING SYSTEM | Android Automotive |
| RADIO | AM/FM/DAB+ |
| INTERNAL STORAGE CAPACITY | 32GB |
| SMARTPHONE INTEGRATION | USB 3.0 socket Wi-Fi connectivity Android Auto / Apple CarPlay compatible Phone storage pocket |

| DRIVER CONTROLS | |
|--------------------------------|--|
| SAFETY SYSTEMS | AEB on/off, DWS on/off/sensitivity adjust, LDW on/off/sensitivity adjust, TMW on/off, ESC&ASR on/off, headlamps and ALS on/off |
| ENGINE | Idle speed control Cruise control DPD manual regeneration switch |
| TRANSMISSION (AMT ONLY) | Slow/fast gear engagement control, 1st gear start and normal/economy gear selection modes. Gear selection control with P-R-N-D and sequential shift positions |
| GENERAL CONTROLS | Windscreen wipers (2 speed and intermittent modes), washers, exhaust brake, turn signals |


| INSTRUMENTATION | |
|----------------------------------|---|
| MULTI INFORMATION DISPLAY | AEB, FCW, DWS, LDW, TMW systems activation alerts Single cab: CTW indicator Vehicle systems status Low fuel level alert Fuel consumption information Service interval alerts Hourmeter Adjustable vehicle speed warning |
| GENERAL INSTRUMENTATION | Speedometer and tachometer Digital odometer with integrated dual tripmeters Engine coolant temperature and fuel level gauges |

NNR 55/45-150 AMT IFS TRAYPACK NNR 45-150 AMT IFS TRAYPACK CREW

ISUZU
RELIABILITY IS EVERYTHING

| WEIGHTS (kg) | | | | | | | |
|----------------------------------|---------------|---------|----------------------------|-------|----------|-------|-------|
| MODELS | RATINGS* | | LOADING LIMIT* (at ground) | | WEIGHT # | | |
| | GVM | GCM | FRONT | REAR | FRONT | REAR | TOTAL |
| NNR 55/45-150 AMT IFS TRAYPACK | 5,500 / 4,500 | 8,000** | 2,360 | 4,480 | 1,645 | 1,020 | 2,665 |
| NNR 45-150 AMT CREW IFS TRAYPACK | 4,500 | 8,000** | 2,360 | 4,480 | 1,730 | 1,075 | 2,805 |

* Vehicle ratings and axle weight limits are subject to government regulatory requirements and weight distribution analysis. Consult your Isuzu dealer to select the correct vehicle for your specific application.**4,000 kg maximum towing limit applies to 4,500 kg GVM rated vehicle. Tag trailer weight should not exceed towing vehicle weight. Limit is subject to government regulatory requirements.
#Vehicle as supplied and including 10 litres of fuel.



| |
|--|
| TURNING CIRCLE (kerb to kerb) |
| 10.7 m |

| PERFORMANCE (calculated - typical paved road) | | | | |
|---|-----------------|--|--|--|
| | | GEARED SPEED* (top gear at peak power engine rpm) | LOW SPEED GRADEABILITY (lowest forward gear assuming no wheel slip) | ENGINE SPEED (top gear at 100 km/h) |
| NNR 45-150 AMT TRAYPACK | At 4,500 kg GVM | 111 km/h @ 2,800 rpm | 58% | 2,530 rpm |
| NNR 55-150 AMT TRAYPACK | At 5,500 kg GVM | 111 km/h @ 2,800 rpm | 47% | 2,530 rpm |

* Maximum speed achievable depends on vehicle frontal area as well as other factors. Consult your Isuzu dealer for more detailed information.

| ORDER CODES | |
|--------------------------------------|--------------|
| MODELS | CODES |
| NNR 55/45-150 AMT MWB IFS55 TRAYPACK | NH-NNRAA-SA1 |
| NNR 45-150 AMT CREW IFS45 TRAYPACK | NH-NNRCA-DA1 |

Subject to the conditions outlined in the IAL New Vehicle Warranty, 4x2 Isuzu N series models carry a standard factory warranty which covers the owner for the first 72 months or 250,000 kilometres (whichever comes first). All Isuzu warranties are subject to mandatory prescribed terms under Australian Consumer Law including consumer guarantees. The installed Body and associated equipment carry a standard warranty which covers the owner for the first 36 months. For more details visit the Isuzu website at www.isuzu.com.au which explains Isuzu warranties in more detail, or alternatively contact your local Isuzu Truck dealer. All warranties commence from date of initial delivery.

ISUZU AUSTRALIA LIMITED ABN 97 006 962 572 ("IAL"). The information in this spec sheet was correct at time of printing, but all measurements, specifications and equipment are subject to change without notice. Some equipment may have been changed and/or is available at extra cost. IAL may make changes at any time without notice, in prices, colours, materials, equipment and models. IAL makes all reasonable attempts to ensure the availability of all vehicles and equipment. The information in this spec sheet is general in nature. Your Isuzu dealer can confirm all measurements, specifications and vehicle / equipment availability upon request. To the extent permitted by the law, IAL is not liable to any person as result of reliance on the content of this spec sheet.